

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

TOOLWAY Foam Cleaner 500ml

Date of issue: 2023-12-03

Revision date: 2024-06-26

Version: 1.5

1. IDENTIFICATION

A. Product name

- TOOLWAY Foam Cleaner 500 ml

B. Recommended use and restriction on use

- General use : Urethane foam spray cleaning and cleaning agent
- Restriction on use : Restrictions on the use of closed areas and firearms

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Toolway Industries Ltd
- Address : 280 Hunter's Valley Rd #1, Woodbridge, ON L4H 3V9
- Emergency telephone number : (905) 326-5450

2. HAZARD IDENTIFICATION

A. GHS Classification

- Aerosols : Category1
- Gases under pressure : Liquefied gas
- Serious eye damage/irritation : Category2
- Germ cell mutagenicity : Category1B
- Carcinogenicity : Category2
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H222 Extremely flammable aerosol
- H229 Pressurised container: May burst if heated
- H280 Compressed gas ; Contains gas under pressure; may explode if heated
- H319 Causes serious eye irritation
- H336 May cause drowsiness and dizziness.
- H340 May cause genetic defects
- H351 Suspected of causing cancer

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

2) Response

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Acetone	Dimethyl ketone ; Methyl ketone ; Ketone propane ; Beta-ketopropane ; 2-Propanone ; Propanone ; Dimethyl formaldehyde ; Dimethylketal ; Acetone oil ;	67-64-1	45 ~ 55
2-Propanol	Isopropanol ; Dimethylcarbinol ; Isopropyl alcohol ; n-Propan-2-ol ; Propan-2-ol ; i-Propyl alcohol ; 2-Propanol	67-63-0	20 ~ 30
2-Methylpropane	Propane, 2-methyl- ; 1,1-Dimethylethane ; i-Butane ; iso-Butane ; Trimethylmethane ;	75-28-5	10 ~ 20
Propane	Dimethylmethane ; Propyl hydride ; n-Propane ; Propyldihydride ;	74-98-6	1 ~ 10
Butane	N-Butane ; Butyl hydride ; Methylenehydromethane ;	106-97-8	1 ~ 5

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Accidental contact with liquefied gas or refrigerated liquefied gas may cause burn, severe mayhem and perfrigeration, so please take emergency medical action.
- Get medical attention immediately.
- In case of accidental contact with liquefied gas or refrigerated liquefied gas, warm up the contact part with lukewarm water.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.

- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Causes serious eye irritation
- Compressed gas ; Contains gas under pressure; may explode if heated
- Extremely flammable aerosol
- May cause drowsiness and dizziness.
- May cause genetic defects

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE**A. Precautions for safe handling**

- Avoid contact with incompatible materials.

- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- **ACGIH TLV**
 - [Acetone] : TWA, 250 ppm STEL, 500 ppm
 - [2-Propanol] : TWA, 200 ppm (491 mg/m³), STEL, 400 ppm (984 mg/m³)
 - [2-Methylpropane] : STEL 1000 ppm
 - [Propane] : Asphyxia
 - [Butane] : STEL 1000 ppm
- **OSHA PEL**
 - [Acetone] : 1000 ppm, 2400 mg/m³
 - [2-Propanol] : 400 ppm, 980 mg/m³
 - [Propane] : 1000 ppm, 1800 mg/m³

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

- **Respiratory protection**
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Consider warning properties before use.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- **Eye protection**
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- **Hand protection**
 - Wear appropriate chemical resistant glove.
- **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Not available
B. Odor	제품 특이취
C. Odor threshold	Not available
D. pH	Not available

E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	Not available
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	Not available
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical Stability

- high-pressure gas; May explode when heated.

B. Possibility of hazardous reactions

- Contact with other combustible material may cause fire.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- ☐ **Respiratory tracts**
 - Not available
- ☐ **Oral**
 - Not available
- ☐ **Eye-Skin**
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- ☐ **Acute toxicity**
 - * **Oral**
 - Product (ATEmix) : >5000mg/kg
 - [Acetone] : LD50 5800 mg/kg Rat (ECHA)
 - [2-Propanol] : LD50 5840 mg/kg Rat (OECD TG 401) (ECHA)
 - * **Dermal**
 - Product (ATEmix) : >5000mg/kg
 - [Acetone] : LD50 > 7426 mg/kg Rabbit (ECHA)
 - [2-Propanol] : LD50 12800 mg/kg (16.4 mL/kg) Rabbit (OECD TG 402) (ECHA)
 - * **Inhalation**
 - Product (ATEmix) : >50.0mg/L, Vapour, 4hr
 - [Acetone] : Vapour LC50 114.6 mg/L 4 hr Rat (55700 ppm 3 hr) (ECHA)

- [2-Propanol] : Vapor LC50 > 30.1 mg/L 4 hr (>10000 ppm 6 hr) Rat No death GHS criteria not met (OECD TG 403, GLP) (ECHA)
- [2-Methylpropane] : Gas LC50 > 200000 ppm 4 hr (>800000 ppm 15 min) Rat Not classified (ECHA)
- [Propane] : Gas LC50 < 38890 ppm 4 hr (> 55000 ppm 2 hr) Guinea pig Not classified (ACGIH) (NITE)
- [Butane] : Gas LC50 > 200000ppm 4 hr Rat Not classified (800000ppm 15 min) (Read-across 74-98-6) (ECHA)
- ☐ **Skin corrosion/irritation**
 - Not available
- ☐ **Serious eye damage/irritation**
 - Causes serious eye irritation
- ☐ **Respiratory sensitization**
 - Not available
- ☐ **Skin sensitization**
 - Not available
- ☐ **Carcinogenicity**
 - * **IARC**
 - [2-Propanol] : Group 3
 - * **OSHA**
 - Not available
 - * **ACGIH**
 - [Acetone] : A4
 - [2-Propanol] : A4
 - * **NTP**
 - Not available
 - * **EU CLP**
 - [2-Methylpropane] : Carc.1A (isobutane (containing ≥ 0.1% butadiene (203-450-8)))
 - [Butane] : Carc.1A (butane (containing ≥ 0.1% butadiene (203-450-8)))
- ☐ **Germ cell mutagenicity**
 - May cause genetic defects
- ☐ **Reproductive toxicity**
 - Not available
- ☐ **STOT-single exposure**
 - May cause drowsiness and dizziness.
- ☐ **STOT-repeated exposure**
 - Not available
- ☐ **Aspiration hazard**
 - Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- ☐ **Fish**
 - [Acetone] : LC50 6210 ~ 8120 mg/L 96 hr Pimephales promelas (OECD TG 203) (ECHA)
 - [2-Propanol] : LC50 9640 mg/L 96 hr Pimephales promelas (ECHA)
- ☐ **Crustaceans**
 - [Acetone] : LC50 8800 mg/L 48 hr Daphnia pulex, NOEC 2212 mg/L 28 d Daphnia magna (ECHA)
- ☐ **Algae**
 - [Acetone] : EC50 6415 mg/L 48 hr Raphidocelis subcapitata (OECD TG 201) (ECHA)

B. Persistence and degradability

- ☐ **Persistence**
 - [Acetone] : log Pow - 0.23 (calculation) (ECHA)
 - [2-Propanol] : log Pow 0.05 (25 °C) (ECHA)
 - [2-Methylpropane] : log Pow 1.09 (Read-across CAS No. 74-82-8) (ECHA)
 - [Butane] : log Kow 2.89 (HSDB)
- ☐ **Degradability**
 - Not available

C. Bioaccumulative potential

☐ **Bioaccumulative potential**

- [Acetone] : BCF 0.69 (ECHA)

☐ **Biodegradation**

- [Acetone] : Readily biodegradable, 90.9 % 28 d (CO₂ evolution) (OECD TG 301 B) (ECHA)
- [2-Propanol] : Readily biodegradable, BOD₅/COD ratio ≥ 0.5 (EU Method C.5 and EU Method C.6) (ECHA)
- [2-Methylpropane] : Readily biodegradable (ECHA)
- [Butane] : 100 % 385.5 hr, Readily biodegradable (Read across 74-84-0) (ECHA)

D. Mobility in soil

- [2-Propanol] : log K_{oc} 0.03 (SIDS)

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1950

B. Proper shipping name

- AEROSOLS

C. Hazard Class

- 2.1

D. IMDG CODE/IATA DGR Packing group

- Not applicable

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-D (Flammable gases)
- EmS SPILLAGE SCHEDULE : S-U (Gases (flammable, toxic or corrosive))

15. REGULATORY INFORMATION

A. National and/or international regulatory information

☐ **POPs Management Law**

- [Acetone] : Not applicable
- [2-Propanol] : Not applicable
- [2-Methylpropane] : Not applicable
- [Propane] : Not applicable
- [Butane] : Not applicable

○ **Information of EU Classification**

* **Classification**

- [Acetone] : H225,H319,H336
- [2-Propanol] : H225,H319,H336
- [2-Methylpropane] : H220,H280,H340,H350
- [Propane] : H220,H280
- [Butane] : H220,H280,H340,H350

○ **U.S. Federal regulations**

* **OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

* **CERCLA Section 103 (40CFR302.4)**

- [Acetone] : 2267.995 kg 5000 lb

* **EPCRA Section 302 (40CFR355.30)**

- Not applicable

* **EPCRA Section 304 (40CFR355.40)**

- Not applicable

* **EPCRA Section 313 (40CFR372.65)**

- [2-Propanol] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2023-12-03

C. Revision number and Last date revised

- 5 times, 2024-06-26

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).